



# DC BLOCK

# MODEL WA8055H/6

10 MHz – 6.0 GHz

200 VOLTS



## Features

Inner Only - 6 GHz SMA DC Block

5/16 hex provides secure torquing surface for mating in hard to get at places.

## Specifications

Nominal Impedance: 50 ohms

Frequency Range: 10 MHz to 6 GHz

Maximum VSWR: 1.35

Maximum Insertion Loss: 0.5 dB

Frequency GHz	Insertion Loss (dB)	VSWR (Max)
0.01—1.0	0.25	1.20
1.0—6.0	0.50	1.35

Voltage: 200 volts

Temperature Range: -65°C to + 125°C

Connectors: SMA M/F connectors per MIL-STD-348 Interface dimension mate nondestructively with MIL-C-39012 connectors.

Construction: Stainless steel body with stainless steel connectors with gold plated beryllium copper female contact and stainless steel male contact.

## Physical Dimensions:

Model	Conn.	Length	Wt.
8055H/6-21	Male – Female	22.35 (0.88)	3.9 gm 0.14 oz
8055H/6-11	Female – Female	Call	N/A
8055H/6-22	Male - Male	Call	N/A



## WEINSCHTEL ASSOCIATES

TEL: 877.948.8342 / 301.963.4630 ♦ Fax: 301.963.8640

WEB: <http://www.WeinschelAssociates.com>

EMAIL: [sales@WeinschelAssociates.com](mailto:sales@WeinschelAssociates.com)

Version 1.0.1

Specification  
Subject to  
change without  
notice