


# Broadband Resistive Power Divider MODEL WA1575

DC – 40.0 GHz

1 WATT



## AMPLITUDE & PHASE TRACKING (MAX.)

Frequency (GHz)	Tracking	
	Amplitude	Phase
DC – 40.0	< 0.25	< 2 °

## Features

**Lightweight Miniature package:** High power capability. These resistive power dividers are intended for RF and wireless applications in which the signal must be divided or combined.

## Specifications

**NOMINAL IMPEDANCE:** 50Ω

**FREQUENCY RANGE:** DC - 40.0 GHz

**INSERTION LOSS:** 6 dB nominal, 10.5 dB maximum (between input and either output).

**MAXIMUM INPUT POWER:** 1.0 watt CW, 1kw peak (5 μsec pulse width, 0.05 % duty cycle, input connector only).

**TEMPERATURE RANGE:** -55°C to +125 °C

**TEMPERATURE COEFFICIENT:** < 0.004 dB/dB/°C

**POWER COEFFICIENT:** < 0.005 dB/dB/watt

**CONSTRUCTION:** Nickel plated brass body; stainless steel connectors.

## MAXIMUM VSWR

Frequency (GHz)	VSWR
DC – 40.0	1.70

**CONNECTORS:** Male 2.92mm port 1, (2) Female 2.92mm ports 2 and 3; all ports-mate nondestructively with other SMA, 2.92mm and 3.5mm connectors. Optional female 2.92mm connectors are available on all ports.

**WEIGHT:** 25 g ( 0.9 oz ) maximum

## PHYSICAL DIMENSIONS:

**Body Width:** 10.2 (0.40)

**Body Height:** 15.2 (0.60) Square

NOTE: All dimensions are given in mm (inches) and are maximum, unless otherwise specified.



## WEINSCHEL ASSOCIATES

TEL: 877.948.8342 / 301.963.4630 ♦ Fax: 301.963.8640

WEB: <http://www.WeinschelAssociates.com>

EMAIL: [sales@WeinschelAssociates.com](mailto:sales@WeinschelAssociates.com)

127

Specification  
Subject to change  
without notice